



Kwik-Set

Sheetfed Offset

Standard Process Ink

Characteristics	<p>The Kwik-Set is a duct-fresh, fast setting all-round process ink series.</p> <p>It is optimally suited for straight-line printing on all multicolour printing presses.</p> <p>The benefits of Kwik-Set are good print sharpness, good gloss as well as fast setting..</p>																						
Ink setting	Duct-fresh																						
Substrates	Ideal for glossy coated papers/board. Suited for uncoated and matt coated papers/board and partly suited for papers and board.																						
Printing properties	<table border="0"> <tr><td>Dot gain</td><td>6</td></tr> <tr><td>Gloss</td><td>5</td></tr> <tr><td>Setting</td><td>5</td></tr> <tr><td>Oxidative drying</td><td>4</td></tr> <tr><td>Rub resistance</td><td>4</td></tr> <tr><td>Rapid further processing</td><td>4</td></tr> <tr><td>Suitability for glossy coated papers/board</td><td>7</td></tr> <tr><td>Suitability for uncoated papers/board</td><td>4</td></tr> <tr><td>Suitability for matt coated papers/board</td><td>4</td></tr> </table> <p>1 = Characteristic weakly expressed 7 = Characteristic strongly expressed</p>					Dot gain	6	Gloss	5	Setting	5	Oxidative drying	4	Rub resistance	4	Rapid further processing	4	Suitability for glossy coated papers/board	7	Suitability for uncoated papers/board	4	Suitability for matt coated papers/board	4
Dot gain	6																						
Gloss	5																						
Setting	5																						
Oxidative drying	4																						
Rub resistance	4																						
Rapid further processing	4																						
Suitability for glossy coated papers/board	7																						
Suitability for uncoated papers/board	4																						
Suitability for matt coated papers/board	4																						
Remarks and special information	<p>A specific feature of Kwik-Set is it really stable press behaviour.</p> <p>Suited for printing work corresponding to ISO 12647-2.</p>																						
Fastness properties	Light	Alcohol	Solvent mixture	Alkali	Hot calendering																		
<i>Kwik-Set Yellow</i>	5	+	+	+	+																		
<i>Kwik-Set Magenta</i>	5	+	+	-	+																		
<i>Kwik-Set Cyan</i>	8	+	+	+	+																		
<i>Kwik-Set Black, blue toned</i>	8	-	-	+	-																		
	<p>Light fastness: according to DIN 16525 from 1 (low) to 8 (high)</p> <p>+ = Resistance provided</p> <p>- = Resistance not provided</p>																						

Version: 18.04.07

**PO Box 1085 ~ 4745 Adams Road
Hixson, TN. 37343
Phone: (423) 875-4705 Fax: (423) 877-3037**

The aim of our technical documents is to inform and advise our customers. However, the transferability of general values known from experience and laboratory results to concrete practical applications depends on a number of factors which are beyond our control. We therefore ask for your understanding that these advice documents cannot be used as the basis for claims in law.